



[Home](#) > [Products](#) > [Inkjet Printing and Proofing](#) > [VUTEk Superwide Printers](#) > [VUTEk mid-range printers](#) > [EFI VUTEk H2000 Pro](#)

[RESOURCES](#)

[ABOUT EFI](#)

# EFI VUTEk H2000 Pro

How to E

## It's all about growth

Modular in design, the production-level EFI™ VUTEk® H2000 Pro printer with UltraDrop™ Technology is ideal if you are looking to enter into large-format digital printing or want to capture more premium-margin jobs. Available with a number of production and imaging options, you can configure a printing system to match your business needs today or add capability when new opportunities arise.

[Overview](#)[Features](#)[Specifications](#)[Applications](#)[Resources](#)[Support](#)

### Media/Handling

- Handles rigid and sheeted media up to 80 in. (2 m) wide and up to 2 in. (5.08 cm) thick
- Optional roll-to-roll production with the installation of unwinders and rewinders

## Productivity

- Best Quality Mode (1,000 dpi, heavy smoothing): 4 - 4'x8' (1.2 m x 2.4 m) boards per hour or 225 ft<sup>2</sup>/hr (2 m<sup>2</sup>/hr)
- POP Quality Mode (600 dpi, light smoothing): 14 - 4'x8' (1.2 m x 2.4 m) boards per hour or 710 ft<sup>2</sup>/hr (66 m<sup>2</sup>/hr)
- Up to Speed (600 dpi, no smoothing): 20 - 4'x8' (1.2 m x 2.4 m) boards per hour or 1,050 ft<sup>2</sup>/hr (98 m<sup>2</sup>/hr)

## Environmental considerations

- Compressed Air: 95–145 psi maximum at 4 cf/m—dry air only (not included)
- Fully enclosed design for operator safety and environmental considerations
- Temperature: 68° F to 86° F (20° C to 30° C)
- Humidity: 30% to 80% (noncondensing)
- Machine weight: 4550 lbs. (2063.8 kg)
- Height: 65" (165.1 cm)
- Width: 201" (511 cm)
- Depth: 66" (168 cm) without tables
  - + 5" (12.7 cm) unwinder
  - + 5" (12.7 cm) rewinder
- Electrical: 3-Phase, 60 amps @ 200–230 volt supply

## Genuine EFI Inks

- Supplied in 5.0-liter containers
- Expanded gamut CMYK pigments for world-class pantone matching
- EFI pigment dispersions ensure optimized size and concentration for best-in-class ink stability

## Optional EFI Fiery proServer and Fiery XF software

- Optimized for use with the EFI Fiery proServer and Fiery XF DFE
- Bidirectional communication capability between the Fiery
- XF DFE and printer allows back communication of audit information on every print job
- Powerful production tools such as nesting, step and repeat, scaling, cropping and tiling
- Advanced ICC color management for reliable color, quality output and proofing-quality color

## Enhanced Service Program (ESP)

- EFI's industry-leading service and support program for your printer, Fiery proServer hardware and Fiery > software
- Thirteen months of Essential coverage, with 24-business-hour (three-business-day) response
- Eligible for upgrade to:

- Critical: Providing eight-business-hour (one-business-day) response
- ProActive: Providing 16-business-hour (two-business-day) response

[Terms of Use](#) | [Privacy](#) | [Investor Relations](#) | [Careers](#) | [Contact Us](#)

© 2015 Electronics For Imaging. All Rights Reserved.